



Roll up - System

Automatic belt

KONNEX

Never roll up by hand again

Webbing width	:	25 mm
Material	:	Hochfester Stahl
Finishing	:	blau verzinkt
Tested according	:	DIN EN 12195-2
Breaking Strength (BS)	:	7,0 kN (700 daN)
Lashing Capacity (LC)	:	3,5 kN (350 daN)
STF - Value	:	119 daN
Total length	:	5,0 m

Roll up - System 25mm


with safety roll up lock



Art. Nr.: 8AQ25S050501W000

With a roll up system your load is quickly secured. No cumbersome insertion of the webbing into the winding shaft, no free hanging webbing after securing the load. Especially easy to handle. Due to the automatic retractor, the webbing is slightly under tension during the securing process. If the webbing is rewound too quickly, e.g. if the end fitting is released, the system is blocked by the safety rewind lock in the reel spool by means of a locking lever, thus preventing injuries caused by whirling end fittings, and the webbing is rewound in a controlled manner.

Release the webbing in a controlled manner.



Pull out the webbing to unlock it.

- the safest and smartest retractable ratchet harness in the world
- the only retractable ratchet belt in the world certified by TÜV / GS
- fast, easy and safe to use
- built-in spring automatically retracts the webbing for easy storage
- built-in self-locking mechanism to control the retraction speed
- safety retraction lock in case of too fast retraction speed, the best protection for the user
- strong and abrasion resistant polyester webbing

Article available with other end fittings:



S-Hook



S-Hook with Safety device



J-Hook



Flat hook with Safety device



KONNEX B.V.

Gezellenstraat 7
NL - 3861 RD Nijkerk
+31 33 2464128
info@konnexgroup.nl

KONNEX GmbH

Friedrichstraße 295
D - 42551 Velbert
+49 2051 20738-0
info@konnexgroup.de