



# Roll up - System

Automatic belt

# KONNEX

*Never roll up by hand again*

## Roll up - System 35mm

lockable with safety roll up lock




Art. Nr.: BQ35S030500W000

Webbing width	:	35 mm
Material	:	High tensile steel
Finishing	:	blue chromated
Tested according	:	DIN EN 12195-2
Breaking Strength (BS)	:	20,0 kN (2.000 daN)
Lashing Capacity (LC)	:	10,0 kN (1.000 daN)
STF - Value	:	280 daN
Total length	:	5,0 m

With a roll up system your load is quickly secured. No cumbersome insertion of the webbing into the winding shaft, no free hanging webbing after securing the load. Especially easy to handle. Due to the automatic retractor, the webbing is slightly under tension during the securing process. If the webbing is rewound too quickly, e.g. if the end fitting is released, the system is blocked by the safety rewind lock in the reel spool by means of a locking lever, thus preventing injuries caused by whirling end fittings, and the webbing is rewound in a controlled manner.

Release the webbing in a controlled manner.



Pull out the webbing to unlock it.

- the safest and smartest retractable ratchet harness in the world
- the only retractable ratchet belt in the world certified by TÜV / GS
- fast, easy and safe to use
- lockable design > anti-theft protection
- built-in spring automatically retracts the webbing for easy storage
- built-in self-locking mechanism to control the retraction speed
- safety retraction lock in case of too fast retraction speed, the best protection for the user
- strong and abrasion resistant polyester webbing



Article available with other end fittings:



J-Hook



Clow hook



J-Hook with Safety device



J-Hook



MEMBER OF  
KONNEX GROUP

KONNEX B.V.

Gezellenstraat 7  
NL - 3861 RD Nijkerk  
+31 33 2464128  
info@konnexgroup.nl

KONNEX GmbH

Friedrichstraße 295  
D - 42551 Velbert  
+49 2051 20738-0  
info@konnexgroup.de